

Schedule of Aluminum Electrolytic Capacitors' Variety

铝电解电容器品种一览表

用途分类 Type (Use case)	产品型号 Type (Omense)	品名 Product name	使用温度 Temperature range	特点 Feature						额定电压 Rated voltage	容量范围 Capacitance range	漏电流 漏电流值 Capacitor tolerance (%)	页码 Page code
				标准型 Standard type	微型 Miniature	小型化 Low impedance	低阻抗 Low ESR	高耐压 High voltage	长寿命 Long life				
超小型品	CD11C	SM 7mm标准品	-40~+85	●	●					6.3-63	0.1-330	+20	8
	CD11X	SX 7mm高CV品	-40~+85		●					6.3-63	0.1-470	+20	9
	CD11N	SP 7mm无极性品	-40~+85		●					6.3-63	0.1-100	+20	10
	CD21C	ST 7mm高温品	-40~+105		●					6.3-63	0.1-220	+20	11
通用品	CD11	SS 高CV标准品	-40~+85	●						6.3-315	0.1-22000	+20	12
	CD11H	SR 中高压标准品	-25~+85	●	●				●	160-450	0.47-560	+20	14
	CD288	SF 高频低阻抗品	-40~+85			●				6.3-100	0.47-10000	+20	15
	CD71	BP 无极性标准品	-40~+85	●						6.3-100	0.47-6800	+20	16
特殊回路	CD72	NF 无极性音频品	-40~+85	●		●				10-100	0.47-47	+10	17
	CD5	NP 无极性低耗品	-40~+85	●			●			10-100	0.47-47	+10	18
	CD114	SL 低漏电流标准品	-40~+85	●						10-50	0.33-330	+10	19
	CD117	SH 高精度稳定品	-40~+85	●						10-50	0.47-470	+10	20
高信頼品	CD5	TN 宽温无极性品	-40~+105					●		6.3-100	0.47-4700	+20	21
	CD110	SK 高可靠标准品	-40~+85	●						6.3-250	0.1-10000	+20	22
	CD210	TR 宽温度标准品	-40~+105	●				●		6.3-250	0.1-10000	+20	24
	CD260	TK 宽温长寿命品	-40~+105			●		●		10-63	10-3300	+20	26
专用品	CD261	PD 宽低温用品	-40~+105		●	●				6.3-100	1-10000	+20	27
	CD262	PH 宽高温用品	-40~+125		●	●		●		10-63	0.47-1000	+20	28
	CD211	PF 开关电源品	-40~+105		●	●				6.3-100	0.47-1000	+20	29
	CD21S	PS 闪光灯用品	-20~+55	●		●				300	20-370	+20 -10	30

GENERAL INFORMATION FOR APPLICATION

铝电解电容器使用须知

- ① 直流电解电容器只能在直流电路上，其极性必须标明在适当的位置或在导针/端子旁边。
DC Electrolytic capacitor, it can be used on DC circuit on only polarity is marked with "+" and "-" and or "V" only, it is indicated on proper position or side of lead wire/terminal.
- ② 在电路回路中如不清楚或不明确线路的极性时，则建议使用无极性电解电容器。
If unclear or unknown of polarity of circuit indication, Non polar capacitor is recommended to be used.
- ③ 电解电容器的工作环境不能超过规定的使用温度范围。
Capacitors should not be used at the environmental temperature which exceeding the range of spec-fide operating temperature.
- ④ 电解电容器应储存于低温且干燥场所，如储存期较长，则使用前应用额定电压对其重新老化。
Capacitors should be stored in low temperature and dry place, if stored in long time, re-aging process with rated voltage must be taken prior to use capacitor.
- ⑤ 通过电解电容器的纹波电流不应超过其允许范围，如超过了额定值，需选用耐大纹波电流的电解电容器。
Do not allow excessive ripple current to pass, Use the electrolytic capacitor at current values within the permissible ripple range.
- ⑥ 使用时，电解电容器的工作电压不应超过其额定电压。
Applied working voltage to capacitor which do not exceed the rated working voltage of capacitors.
- ⑦ 电烙铁等高温发热装置应与电解电容器塑料外壳保持适当的距离，以防止过热造成塑料管破裂。
Heaters of high temperatures such as soldering irons should be kept away from the vinyl insulation sleeve of capacitor which to avoid the cause made over heat or break down to sleeve.
- ⑧ 在焊接电解电容器时，其焊接时间和焊接温度不应超过10秒钟及260℃。
When soldering the electrolytic capacitor, the soldering time should never be permitted over 10 seconds, and for 260℃ of the soldering temperature.
- ⑨ 对导针、端子，如施加超过规定的力，将会破坏电解电容器的内部结构。
If excessive force is applied to the lead wires or terminals, the inside construction of capacitor should be destroyed.

SX 7mm标准品 (CD11X型)

- 7mm高度, 通用标准品。
Be 7mm in height, for general purpose, standard size.
- 适用于汽车音响、盒式收录机、袖珍计算器等电器。
Used in car audio, cassette tape recorders, pocket calculator circuits, etc.



项目	Item	特性				Characteristics					
尺寸及其误差 Size and its tolerance	ΦD	4	5	6	8						
	F=0.5	1.5	2.0	2.5	3.5	≥ Φ 8壳防漏 ≥ Φ 8 with safety vent PVC壳体 PVC sleeve					
	$\Phi d \pm 0.1$	0.45				0.5					
	α	0.5				0.5					
	β	0.3				0.3					
工作温度范围	Operating temperature range	-40 ~ +85°C									
额定电压范围	Rated voltage range	6.3V ~ 63V DC									
静电容量范围	Nominal capacitance tolerance	0.1 μ F ~ 470 μ F									
静电容量误差	Capacitance tolerance	±20% (100Hz, -20°C)									
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.01CV 或 3 μ A (取较大值) 1分钟 I ≤ 0.01CV 或 3 μ A (whichever is greater) after 1 minute									
		C: 标准静电容量 Normal capacitance V: 额定工作电压 Rated voltage									
损耗角正切	Dissipation factor	额定电压 (V)	6.3	10	16	25	35	50	63	100Hz	
		tg δ (MAX)	0.24	0.20	0.16	0.14	0.12	0.10	0.10	0.10	20°C
温度特性	Temperature characteristics (impedance ratio at 100Hz)	额定电压 (V)	6.3	10	16	25	35	50	63	100Hz	
		Z-25°C/Z+20°C	4	3	2	2	2	2	2	2	
		Z-40°C/Z+20°C	8	6	4	4	3	3	3	3	
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:									
		静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value								
		漏电流	≤ 初期规定值 ≤ initial specified value								
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:									
		静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value								
		漏电流	≤ 初期规定值的200% ≤ 200% of the initial specified value								

		DXL (mm)							
C (μ F)	代码	6.3	10	16	25	35	50	63	
		0J	1A	1C	1E	1V	1H	1J	
0.1	0R1						4X7	0.8	
0.22	R22						4X7	2.0	
0.33	R33						4X7	3.0	
0.47	R47						4X7	4.0	
1	010						4X7	8.5	
2.2	2R2						4X7	14	
3.3	3R3						4X7	17	4X7 19
4.7	4R7						4X7	21	5X7 24
10	100						4X7	27	5X7 32
22	220						4X7	38	5X7 43
33	330						4X7	43	5X7 50
47	470	4X7 35	4X7 38	4X7 43	4X7 49	4X7 56	4X7 63	4X7 70	5X7 77
100	101	4X7 61	4X7 71	4X7 84	4X7 99	4X7 115	4X7 132	4X7 150	4X7 168
220	221	5X7 96	5X7 111	5X7 132	5X7 150	5X7 170	5X7 190	5X7 210	5X7 230
330	331	6X7 123	6X7 145	6X7 170	6X7 195	6X7 220	6X7 245	6X7 270	6X7 295
470	471	8X7 158	8X7 185	8X7 215	8X7 245	8X7 275	8X7 305	8X7 335	8X7 365
									DXL 纹波电流 (mA)

SP 7mm标准品 (CD11N型)

- 7mm高度, 极性可反转积变换。
Be 7mm in height, the polarity can be reversed.
- 适用于信号耦合等极间反转变换的电路。
Used in circuits what polarity is reversed, such as signal coupling, etc.



项目	Item	特性				Characteristics					
尺寸及其误差 Size and its tolerance	ΦD	4	5	6	8						
	F=0.5	1.5	2.0	2.5	3.5	≥ Φ 8壳防漏 ≥ Φ 8 with safety vent PVC壳体 PVC sleeve					
	$\Phi d \pm 0.1$	0.45				0.5					
	α	0.5				0.5					
	β	0.3				0.3					
工作温度范围	Operating temperature range	-40 ~ +85°C									
额定电压范围	Rated voltage range	6.3V ~ 63V DC									
静电容量范围	Nominal capacitance tolerance	0.1 μ F ~ 100 μ F									
静电容量误差	Capacitance tolerance	±20% (100Hz, -20°C)									
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.01CV 或 3 μ A (取较大值) 1分钟 I ≤ 0.01CV 或 3 μ A (whichever is greater) after 1 minute									
		C: 标准静电容量 Normal capacitance V: 额定工作电压 Rated voltage									
损耗角正切	Dissipation factor	额定电压 (V)	6.3	10	16	25	35	50	63	100Hz	
		tg δ (MAX)	0.26	0.22	0.18	0.16	0.14	0.12	0.10	0.10	20°C
温度特性	Temperature characteristics (impedance ratio at 100Hz)	额定电压 (V)	6.3	10	16	25	35	50	63	100Hz	
		Z-25°C/Z+20°C	4	3	2	2	2	2	2	2	
		Z-40°C/Z+20°C	8	6	4	4	3	3	3	3	
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:									
		静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value								
		漏电流	≤ 初期规定值 ≤ initial specified value								
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:									
		静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value								
		漏电流	≤ 初期规定值的200% ≤ 200% of the initial specified value								

		DXL (mm)							
C (μ F)	代码	6.3	10	16	25	35	50	63	
		0J	1A	1C	1E	1V	1H	1J	
0.1	0R1						4X7	0.8	
0.22	R22						4X7	2.0	
0.33	R33						4X7	3.0	
0.47	R47						4X7	4.0	
1	010						4X7	8.5	
2.2	2R2						4X7	14	
3.3	3R3						4X7	17	4X7 19
4.7	4R7						4X7	21	5X7 24
10	100						4X7	27	5X7 32
22	220						4X7	38	5X7 43
33	330						4X7	43	5X7 50
47	470	4X7 35	4X7 38	4X7 43	4X7 49	4X7 56	4X7 63	4X7 70	5X7 77
100	101	4X7 61	4X7 71	4X7 84	4X7 99	4X7 115	4X7 132	4X7 150	4X7 168
220	221	5X7 96	5X7 111	5X7 132	5X7 150	5X7 170	5X7 190	5X7 210	5X7 230
330	331	6X7 123	6X7 145	6X7 170	6X7 195	6X7 220	6X7 245	6X7 270	6X7 295
470	471	8X7 158	8X7 185	8X7 215	8X7 245	8X7 275	8X7 305	8X7 335	8X7 365
									DXL 纹波电流 (mA)

ST 7mm标准品 (CD21C型)

- 7mm高度, 105°C。
Be 7mm in height, 105°C.
- 适用于移动通信、袖珍对讲机、汽车音响等电路。
Used in locomotive communication, pocket intercom telephones, car audio circuits, etc.



项目 Item	特性 Characteristics								
尺寸及其误差 Size and its tolerance 	ΦD	4	5	6	8				
	F±0.5	1.5	2.0	2.5	3.5				
	Φd±0.1	0.45		0.5					
	α	0.5							
	β	0.3							
工作温度范围 Operating temperature range	-40 ~ +85°C								
额定电压范围 Rated voltage range	6.3V ~ 63V DC								
静电容量范围 Nominal capacitance tolerance	0.1 μF ~ 220 μF								
静电容量误差 Capacitance tolerance	±20% (100Hz · 20°C)								
漏电流 (20°C) Leakage current (20°C)	I ≤ 0.01CV 或 3 μA (取其较大值) 1分钟 I ≤ 0.01CV (or 3 μA (whichever is greater) after 1 minute								
损耗角正切 Dissipation factor	额定电压 (V) Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz
	tg δ (MAX)	0.26	0.20	0.18	0.15	0.14	0.12	0.10	20°C
温度特性 Temperature characteristics (impedance ratio at 100Hz)	额定电压 (V) Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz
	Z-25°C / Z+20°C	4	3	2	2	2	2	2	
	Z-40°C / Z+20°C	8	6	4	4	3	3	3	
高温负荷特性 Endurance	85°C 施加额定电压1000小时, 恢复16小时后电容高应满足下表: After applying rated voltage for 1000 hours at 85°C, then resumed 16 hours:								
	静电容量变化 Capacitance change	在初期值的 ±20% 范围内 Within ±20% of the initial measured value							
	tg δ	≤ 初期规定值的 150% ≤ 150% of the initial specified value							
	漏电流 Leakage current	≤ 初期规定值 ≤ initial specified value							
高温贮存特性 Shelf life	105°C, 贮存500小时, 恢复16小时后电容高应满足下表: After storage for 500 hours at 105°C, then resumed 16 hours:								
	静电容量变化 Capacitance change	在初期值的 ±20% 范围内 Within ±20% of the initial measured value							
	tg δ	≤ 初期规定值的 150% ≤ 150% of the initial specified value							
	漏电流 Leakage current	≤ 初期规定值的 200% ≤ 200% of the initial specified value							

		DXL (mm)													
C (μF)	代码 Code	6.3		10		16		25		35		50		63	
		0J	1A	1C	1E	1V	1H	1J	1K	1L	1M	1N	1O	1P	
0.1	0R1											4X7	0.8		
0.22	R22											4X7	2.0		
0.33	R33											4X7	3.0		
0.47	R47											4X7	4.0		
1	010											4X7	8.5		
2.2	2R2											4X7	14		
3.3	3R3											4X7	17	4X7	11
4.7	4R7									4X7	19	5X7	22	5X7	16
10	100					4X7	24	5X7	16	5X7	29	6X7	34	6X7	26
22	220	4X7	29	5X7	33	5X7	37	6X7	19	6X7	45	8X7	53	8X7	40
33	330	5X7	37	5X7	41	6X7	48	6X7	28	8X7	59				
47	470	6X7	44	6X7	54	6X7	57	8X7	45						
100	101	6X7	68	8X7	75	8X7	89								
220	221	8X7	101											ΦDXL	纹波电流 (mA)

SS 高CV标准品 (CD11型)

- 通用标准品, 小型化尺寸。
For general purpose, small-size.
- 适用于黑白电视、盒式收录机、电话机等电路。
Used in white black TV's, radio cassette recorders, telephones circuits, etc.



项目 Item	特性 Characteristics											
尺寸及其误差 Size and its tolerance 	ΦD	5	6	8	10	13	16	18	20			
	F±0.5	2	2.5	3.5	5.0	7.5	10	15	20			
	Φd±0.1	0.5		0.6		0.8						
	α	1.0				1.5		2.0				
	β	0.5				0.8		1.0				
工作温度范围 Operating temperature range	-40 ~ +85°C											
额定电压范围 Rated voltage range	6.3V ~ 10V DC											
静电容量范围 Nominal capacitance tolerance	0.1 μF ~ 22000 μF											
静电容量误差 Capacitance tolerance	±20% (100Hz · 20°C)											
漏电流 (20°C) Leakage current (20°C)	I ≤ 0.02CV 或 5 μA 1分钟 I ≤ 0.02CV (or 5 μA after 1 minute (whichever is greater))						I ≤ 0.03CV 或 10 μA 3分钟 I ≤ 0.03CV (or 10 μA after 3 minute (whichever is greater))					
	允许漏电流 Leakage current C: 标准静电容量 Nominal capacitance V: 额定工作电压 Rated voltage											
损耗角正切 Dissipation factor	额定电压 (V) Rated voltage (V)	6.3	10	16	25	35	50	63	100	160	250	315
	tg δ	0.26	0.22	0.17	0.16	0.13	0.10	0.15	0.10	0.15	0.20	0.20
	静电容量大于 1000 μF 者, 每增加 1000 μF, tg δ 增加 0.02 When capacitance is more than 1000 μF, tg δ will add 0.02 per 1000 μF, addition.											
浪涌电压 (V) Surge voltage (20°C)	额定电压 (V) Rated voltage (V)	6.3	10	16	25	35	50	63	100	160	250	350
	浪涌电压 (V) Surge voltage (V)	8	13	20	32	44	63	79	125	200	250	300
温度特性 Temperature characteristics (impedance ratio at 100Hz)	额定电压 (V) Rated voltage (V)	6.3	10	16	25	35	50	63	100	160	250	315
	Z-25°C / Z+20°C	6	4	3	3	2	1.5	7	7	10		
	Z-40°C / Z+20°C	12	8	6	4	3	2	7	7	10		
高温负荷特性 Endurance	85°C 施加额定电压1000小时, 恢复16小时后电容高应满足下表: After applying rated voltage for 1000 hours at 85°C, then resumed 16 hours:											
	静电容量变化 Capacitance change	在初期值的 ±20% 范围内 Within ±20% of the initial measured value										
	tg δ	≤ 初期规定值的 150% ≤ 150% of the initial specified value										
	漏电流 Leakage current	≤ 初期规定值 ≤ initial specified value										
高温贮存特性 Shelf life	85°C, 贮存500小时, 恢复16小时后电容高应满足下表: After storage for 500 hours at 85°C, then resumed 16 hours:											
	静电容量变化 Capacitance change	在初期值的 ±20% 范围内 Within ±20% of the initial measured value										
	tg δ	≤ 初期规定值的 150% ≤ 150% of the initial specified value										
	漏电流 Leakage current	≤ 初期规定值的 200% ≤ 200% of the initial specified value										
备注 Note	如有需要, 可提供引线成型品或编带品 The products can be forming or taping customer need											

SX 7mm标准品 (CD11X型)

- 7mm高度, 通用标准品。
Be 7mm in height, for general purpose, standard size.
- 适用于汽车音响、盒式收录机、袖珍计算器等电器。
Used in car audio, cassette tape recorders, pocket calculator circuits, etc.



项目	Item	特性				Characteristics							
尺寸及其误差 Size and its tolerance	ΦD	4	5	6	8								
	F=0.5	1.5	2.0	2.5	3.5	≥ Φ 8壳防漏 ≥ Φ 8 shell safety vent							
	$\Phi d \pm 0.1$	0.45			0.5	PVC 套管 PVC sleeve							
	α	0.5											
	β	0.3											
工作温度范围	Operating temperature range	-40 ~ +85 °C											
额定电压范围	Rated voltage range	6.3V ~ 63V DC											
静电容量范围	Nominal capacitance tolerance	0.1 μ F ~ 470 μ F											
静电容量误差	Capacitance tolerance	±20% (100Hz, -20°C)											
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.01CV 或 3 μ A (取较大值) 1分钟 I ≤ 0.01CV 或 3 μ A (whichever is greater) after 1 minute											
	允许漏电流	Leakage current	C: 标准静电容量			V: 额定工作电压			Rated voltage				
损耗角正切	Dissipation factor	额定电压 (V)	Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz		
		tg δ (MAX)		0.24	0.20	0.16	0.14	0.12	0.10	0.10	0.10	20°C	
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz		
		Z-25°C/Z+20°C		4	3	2	2	2	2	2	2		
		Z-40°C/Z+20°C		8	6	4	4	3	3	3			
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:											
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内			Within ±20% of the initial measured value						
		tg δ		≤ 初期规定值的150%			≤ 150% of the initial specified value						
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:											
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内			Within ±20% of the initial measured value						
		tg δ		≤ 初期规定值的150%			≤ 150% of the initial specified value						
		漏电流	Leakage current	≤ 初期规定值的200%			≤ 200% of the initial specified value						

		DXL (mm)							
C (μ F)	代码	6.3	10	16	25	35	50	63	
		0J	1A	1C	1E	1V	1H	1J	
0.1	0R1						4X7	0.8	
0.22	R22						4X7	2.0	
0.33	R33						4X7	3.0	
0.47	R47						4X7	4.0	
1	010						4X7	8.5	
2.2	2R2						4X7	14	
3.3	3R3						4X7	17	4X7 19
4.7	4R7						4X7	21	5X7 24
10	100						4X7	27	5X7 32
22	220						4X7	38	5X7 43
33	330						4X7	43	5X7 50
47	470	4X7 35	4X7 38	4X7 43	5X7 49	6X7 56	8X7(9) 95		
100	101	4X7 61	5X7 71	6X7 84	8X7(9) 95				
220	221	5X7 96	6X7 111	8X7(9) 132					
330	331	6X7 123	8X7(9) 145						
470	471	8X7(9) 158							
									φ DXL 纹波电流 (mA)

SP 7mm标准品 (CD11N型)

- 7mm高度, 极性可反转积变换。
Be 7mm in height, the polarity can be reversed.
- 适用于信号耦合等极间反转变换的电路。
Used in circuits what polarity is reversed, such as signal coupling, etc.



项目	Item	特性				Characteristics							
尺寸及其误差 Size and its tolerance	ΦD	4	5	6	8								
	F=0.5	1.5	2.0	2.5	3.5	≥ Φ 8壳防漏 ≥ Φ 8 shell safety vent							
	$\Phi d \pm 0.1$	0.45			0.5	PVC 套管 PVC sleeve							
	α	0.5											
	β	0.3											
工作温度范围	Operating temperature range	-40 ~ +85 °C											
额定电压范围	Rated voltage range	6.3V ~ 63V DC											
静电容量范围	Nominal capacitance tolerance	0.1 μ F ~ 100 μ F											
静电容量误差	Capacitance tolerance	±20% (100Hz, -20°C)											
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.01CV 或 3 μ A (取较大值) 1分钟 I ≤ 0.01CV 或 3 μ A (whichever is greater) after 1 minute											
	允许漏电流	Leakage current	C: 标准静电容量			V: 额定工作电压			Rated voltage				
损耗角正切	Dissipation factor	额定电压 (V)	Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz		
		tg δ (MAX)		0.26	0.22	0.18	0.15	0.14	0.12	0.10	0.10	20°C	
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	Rated voltage (V)	6.3	10	16	25	35	50	63	100Hz		
		Z-25°C/Z+20°C		4	3	2	2	2	2	2	2		
		Z-40°C/Z+20°C		8	6	4	4	3	3	3			
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:											
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内			Within ±20% of the initial measured value						
		tg δ		≤ 初期规定值的150%			≤ 150% of the initial specified value						
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:											
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内			Within ±20% of the initial measured value						
		tg δ		≤ 初期规定值的150%			≤ 150% of the initial specified value						
		漏电流	Leakage current	≤ 初期规定值的200%			≤ 200% of the initial specified value						

		DXL (mm)							
C (μ F)	代码	6.3	10	16	25	35	50	63	
		0J	1A	1C	1E	1V	1H	1J	
0.1	0R1						4X7	0.8	
0.22	R22						4X7	2.0	
0.33	R33						4X7	3.0	
0.47	R47						4X7	4.0	
1	010						4X7	8.5	
2.2	2R2						4X7	14	
3.3	3R3						4X7	17	4X7 19
4.7	4R7						4X7	21	5X7 24
10	100						4X7	27	5X7 32
22	220						4X7	38	5X7 43
33	330						4X7	43	5X7 50
47	470	4X7 35	4X7 38	4X7 43	5X7 49	6X7 56	8X7(9) 95		
100	101	4X7 61	5X7 71	6X7 84	8X7(9) 95				
220	221	5X7 96	6X7 111	8X7(9) 132					
330	331	6X7 123	8X7(9) 145						
470	471	8X7(9) 158							
									φ DXL 纹波电流 (mA)

SS 高CV标准口品 (CD11型)

- 外型尺寸 Case size
- 允许纹波电流 Permitt ripple current

DXL(mm)

C(μF)	WV(V)	DXL(mm)							
		6.3 0J	10 1A	16 1C	25 1E	35 1V	50 1H	DXL(mm)	
0.1	0R1							5X11	0.8
0.22	R22							5X11	2.0
0.33	R33							5X11	3.0
0.47	R47							5X11	4.0
1	010							5X11	8.5
2.2	2R2							5X11	15
3.3	3R3							5X11	20
4.7	4R7							5X11	25
10	100							5X11	30
22	220							5X11	42
33	330							5X11	42
47	470							5X11	42
100	101	5X11	78	5X11	78	5X11	67	5X11	65
220	221	5X11	153	6X12	187	6X12	221	6X12	271
330	331	6X12	230	6X12	247	8X12	316	10X13	374
470	471	6X12	272	8X12	298	8X12	374	10X13	442
1000	102	8X12	459	10X13	527	10X16	604	13X20	706
2200	222	10X20	765	10X20	825	13X20	978	13X25	1105
3300	332	10X20	893	13X20	1063	13X25	1190	16X25	1403
4700	472	13X20	1148	13X25	1275	16X25	1445	16X32	1743
6800	682	13X25	1360	16X25	1576	16X36	1828	18X36	2168
10000	103	16X25	1700	16X36	1998	18X36	2296		
15000	153	16X36	2168	18X36	2196	20X40	2890		
22000	223	18X40	2720	18X40	2655				

C(μF)	WV(V)	DXL(mm)							
		6.3 1J	100 2A	160 2C	200 2D	250 2E	315 2F	DXL(mm)	
2.2	2R2							6X12	24
3.3	3R3							6X12	28
4.7	4R7							6X12	35
10	100							6X12	56
22	220	5X11	85	6X12	111	10X16	81	10X20	84
33	330	6X12	119	8X12	153	10X20	102	13X20	119
47	470	10X13	145	10X13	196	13X20	136	13X20	145
100	101	10X16	255	10X20	315	13X25	204	16X32	213
220	221	10X20	400	13X25	527	16X36	323	18X36	332
330	331	13X20	604	13X25	646	18X40	417		
470	471	16X25	765	16X25	850				
1000	102	10X36	1110	18X36	1173				
2200	222	8X7	1740						

SR 中高压标准品 (CD11H型)

- 适用于高电压、标准尺寸
Middle and high voltage, for general purpose, standard size.
- 适用于节能灯镇流器、开关电源等电路。
Used in energy-saving electronic ballasts, switching power supply, etc.



项目	Item	特性	C(μF)系列								
尺寸及其误差 Size and its tolerance	ΦD	6 8 10 13 16 18 20 22	≥ Φd先防漏 ≥ Φd with safety vent PVC母管 PVC sleeve								
	F±0.05	2.5 3.5 5.0 7.5 10									
	Φd±0.1	0.5 0.6									
	α	1.0 1.5 2.0									
	β	0.5 0.8 1.0									
工作温度范围	Operating temperature range	-25 ~ +85℃									
额定电压范围	Rated voltage range	160V ~ 450V DC									
静电容量范围	Nominal capacitance tolerance	±20% (100Hz · 20℃)									
静电容量误差	Capacitance tolerance	±20% (100Hz · 20℃)									
漏电流 (20℃)	Leakage current (20℃)	I ≤ 0.03CV 或 10μA (取较大值) 3分钟 ≤ 0.03CV or 10μA (whichever is greater) after 3 minute									
损耗角正切	Dissipation factor	允许漏电流	Leakage current	C:标准静电容量	Nominal capacitance	V:额定工作电压	Rated voltage				
		额定电压 (V)	Rated voltage(V)	160	200	250	315	350	400	450	100Hz
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	tg δ (MAX)	0.20	0.20	0.20	0.20	0.25	0.25	0.25	20℃	
		额定电压 (V)	Rated voltage(V)	160	200	250	315	350	400	450	100Hz
高温耐热性	Endurance	85℃ 施加额定电压1000小时, 恢复16小时后静电容量测定下表: After applying rated voltage for 1000 hours at 85℃ then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							Within ±20% of the initial measured value
		tg δ	≤ 初期规定值的150%	≤ 150% of the initial specified value							
		漏电流	Leakage current	≤ 初期规定值							≤ initial specified value
高温贮存特性	Shelf life	85℃, 贮存500小时, 恢复16小时后静电容量测定下表: After storage for 500 hours at 85℃ then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							Within ±20% of the initial measured value
		tg δ	≤ 初期规定值的150%	≤ 150% of the initial specified value							
		漏电流	Leakage current	≤ 初期规定值的200%							≤ 200% of the initial specified value

C(μF)	WV(V)	DXL(mm)											
		160 2C	200 2D	250 2E	315 2F	350 2V	400 2G	450 2W	DXL(mm)				
0.47	R47	6X12	10	10	10								
1	010	6X12	14	6X12	14	6X12	14	8X12	15	8X12	15	10X13	16
2.2	2R2	6X12	22	6X12	26	8X12	26	8X12	26	10X13	24	10X13	24
3.3	3R3	8X12	30	8X12	30	10X13	30	10X13	30	10X16	30	10X16	30
4.7	4R7	8X12	34	10X13	38	10X13	38	10X20	38	10X16	34	10X20	38
10	100	10X13	55	10X16	60	10X20	60	13X25	60	13X20	60	13X25	64
22	220	10X20	94	10X20	94	13X25	111	16X25	102	16X25	94	16X25	94
33	330	13X20	128	13X25	136	13X25	135	16X32	128	16X32	119	16X32	128
47	470	13X25	153	16X25	153	16X25	179	18X40	162	18X36	167	18X36	167
100	101	16X25	255	16X32	281	18X36	299	20X40	280	22X40	306	22X40	315
150	151	16X36	357	18X36	383	18X40	391	22X40	383	22X40			
220	221	18X36	494	18X40	442	20X40	451	25X40	502				
270	271	18X40	459	20X40	485	22X40	510						
330	331	20X40	510	22X40	570	25X35	512						
390	391	22X40	493	25X35	655	25X40	672						
470	471	25X35	680	25X40	723								
560	561	25X40	782										

NF 无极性音频品 (CD72型)

- 低损耗角正切, 高纹波电流。
Low dissipation factor, high ripple current.
- 适用于音频网络分频电路。
Used in speaker dividing network circuits.



项目	Item	特性					Characteristics				
尺寸及其误差	Size and its tolerance	ϕD	8	10	13	16	$\geq \phi 8$ 的槽 $\geq \phi 8$ 的防磨 PVC底座 PVC sleeve				
		F ± 0.5	3.5	5.0	7.5	7.5					
		$\phi d \pm 0.1$	0.5	0.6	0.5						
		α	1.0	1.5							
		β	0.5	0.8							
工作温度范围	Operating temperature range	-40 ~ +85°C									
额定电压范围	Rated voltage range	10V ~ 10V/DC									
静电容量范围	Nominal capacitance tolerance	0.47 μ F ~ 47 μ F									
静电容量误差	Capacitance tolerance	$\pm 10\%$ (100Hz ~ 20°C)									
漏电流 (20°C)	Leakage current (20°C)	1 ≤ 0.03 CV 或 5 μ A (取其较大值) 1分钟 1 ≤ 0.03 CV or 5 μ A (whichever is greater) after 1 minute									
		允许漏电流	Leakage current	C标准静电容量	Nominal capacitance	V额定工作电压	Rated voltage				
损耗角正切	Dissipation factor	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		tg δ (MAX)	0.10	0.08	0.06	0.05	0.05	0.04	0.04	0.04	20°C
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		Z-25°C/Z+20°C	3	2	2	2	2	2	2	2	
		Z-40°C/Z+20°C	8	6	5	4	4	3	3		
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 $\pm 20\%$ 范围内							Within $\pm 20\%$ of the initial measured value
		漏电流	Leakage current	\leq 初期规定值的150%							$\leq 150\%$ of the initial specified value
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 $\pm 20\%$ 范围内							Within $\pm 20\%$ of the initial measured value
		漏电流	Leakage current	\leq 初期规定值的200%							$\leq 200\%$ of the initial specified value

		DXL(mm)											
C(μ F)	代号	10	16	25	35	50	63	100	100	100	100		
		1A	1C	1E	1V	1V	1V	1V	1V	1V	2A		
0.47	R47					8X12	0.8	10X12	0.9	10X16	1.1		
0.68	R68					10X12	1.0	10X16	1.7	10X20	1.5		
1.0	R10				8X12	1.1	10X12	1.3	10X16	1.4	10X20	1.9	
1.5	R15				8X12	1.3	10X12	1.5	10X16	1.8	10X20	2.3	
2.2	R25												
3.3	R33	8X12	1.5	10X12	1.7	10X16	2.1	10X20	2.4	13X20	2.8	13X25	3.2
4.7	R47	10X13	2.0	10X16	2.5	10X20	3.2	10X20	3.5	13X20	3.7	13X25	4.7
6.8	R68	10X13	2.4	10X16	3.0	10X20	3.8	13X20	4.5	13X25	5.0	16X25	5.9
10	R10	10X16	3.2	10X20	4.0	13X20	4.9	13X25	6.1	16X25	6.4	16X25	7.2
15	R15	10X16	3.9	10X20	4.9	13X20	6.1	13X25	7.5	16X25	7.9		
22	R22	10X20	5.3	13X20	6.4	13X25	8.2	16X25	9.5				
33	R33	13X20	7.0	13X25	8.7	16X25	10.6						
47	R47	13X25	9.3	16X25	11.0								

NP 无极性低耗品 (CD S型)

- 高频低损耗, 高纹波电流。
Small loss at high frequency, high ripple current.
- 适用于电机水平偏转电流校正电路。
Used in correction of horizontal deflection current in TVs.



项目	Item	特性					Characteristics				
尺寸及其误差	Size and its tolerance	ϕD	10	13	16	18	$\geq \phi 8$ 的槽 $\geq \phi 8$ 的防磨 PVC底座 PVC sleeve				
		F ± 0.5	5.0	7.5	7.5						
		$\phi d \pm 0.1$	0.6	0.8							
		α	1.5	2.0							
		β	0.8	1.0							
工作温度范围	Operating temperature range	-40 ~ +85°C									
额定电压范围	Rated voltage range	10V ~ 10V/DC									
静电容量范围	Nominal capacitance tolerance	0.47 μ F ~ 47 μ F									
静电容量误差	Capacitance tolerance	$\pm 10\%$, $\pm 20\%$ (100Hz ~ 20°C)									
漏电流 (20°C)	Leakage current (20°C)	1 ≤ 100 μ A 5分钟									
		1 ≤ 100 μ A 5 minute									
损耗角正切	Dissipation factor	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		tg δ (MAX)	0.08	0.06	0.05	0.04	0.04	0.03	0.03	0.03	20°C
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		Z-25°C/Z+20°C	3	2	2	2	2	2	2	2	
		Z-40°C/Z+20°C	8	6	5	4	4	3	3		
高温负荷特性	Endurance	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 $\pm 15\%$ 范围内							Within $\pm 15\%$ of the initial measured value
		漏电流	Leakage current	\leq 初期规定值的150%							$\leq 150\%$ of the initial specified value
高温贮存特性	Shelf life	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 $\pm 15\%$ 范围内							Within $\pm 15\%$ of the initial measured value
		漏电流	Leakage current	\leq 初期规定值的200%							$\leq 200\%$ of the initial specified value

		DXL(mm)									
C(μ F)	代号	10	16	25	35	50	63	100	100	100	100
		1A	1C	1E	1V	1V	1V	1V	1V	1V	2A
0.47	R47										
0.68	R68										
1.0	R10					10X20	1.7	10X20	1.9	13X20	2.0
1.5	R15					10X20	2.1	13X20	2.4	13X25	2.7
2.2	R25										
3.3	R33	10X12	2.4	13X20	3.0	13X25	3.6	16X25	4.3	16X32	4.9
4.7	R47	13X20	3.1	13X25	3.9	16X25	4.6	16X32	5.9	16X36	6.2
6.8	R68	13X25	4.2	16X25	5.1	16X32	6.3	16X36	7.5	18X36	7.7
10	R10	16X25	5.3	16X32	6.9	16X36	8.1	18X36	9.2	18X40	9.8
15	R15	16X32	7.4	16X36	9.0	18X36	10.1	18X40	11.7		
22	R22	16X36	9.5	18X36	11.2	18X40	13				
33	R33	13X36	11.9	18X40	14.5						
47	R47	13X40	15.0								

SL 低漏电标准品 (CD114型)

- 良好的低漏电特性，标准尺寸。
Extremely low leakage current, standard size.
- 适用于有线电视频道转换或小信号输入回路。
Used in TV's frequency channel conversion or weak signal input loop circuits.



项目	Item	特性					Characteristics							
尺寸及其误差 Size and its tolerance		ΦD	5	6.3	8	10	≥Φ8的漏 ≥Φ8 with safety vent PVC塑壳 PVC sleeve							
		F=0.5	2	2.5	2.5	5.0								
		Φd±0.1		0.5		0.6								
		α		1.0		1.5								
		β		0.5		0.8								
工作温度范围	Operating temperature range	-40 ~ +85°C												
额定电压范围	Rated voltage range	10V~50V DC												
静电容量范围	Nominal capacitance tolerance	0.33 μF ~ 330 μF												
静电容量误差	Capacitance tolerance	±20% (100Hz · 20°C)												
漏电流 (20°C)	I _L Leakage current (20°C)	I _L ≤ 0.03CV 或 0.3 μA (取其较大值) 1分钟					I _L ≤ 0.03CV 或 0.3 μA (whichever is greater) after 1 minute							
		1μF 标称静电容量	10	16	25	35	50	100Hz						
损耗角正切	tg δ (MAX)	tg δ (MAX)					0.15	0.12	0.10	0.08	0.08	0.08	20°C	
		Z=25°C, Z=20°C					2	2	1.5	1.5	1.5	1.5	100Hz	
温度特性	Temperature characteristics (impedance ratio at 100Hz)	Z=40°C, Z=20°C					4	3	2	2	2	2		
		85°C 施加额定电压2000小时，恢复16小时后电容容量应满足下表： After applying rated voltage for 2000 hours at 85°C then resumed 16 hours:												
高温负特性	Endurance	静电容量变化					在初期值的 ±15% 范围内							Within ±15% of the initial measured value
		漏电流					≤ 初期规定值							≤ initial specified value
		漏电流					≤ 初期规定值的150%							≤ 150% of the initial specified value
高温贮存特性	Shelf life	静电容量变化					在初期值的 ±15% 范围内							Within ±15% of the initial measured value
		漏电流					≤ 初期规定值的200%							≤ 200% of the initial specified value
		漏电流					≤ 初期规定值的150%							≤ 150% of the initial specified value

		DXL (mm)										
C (μF)	代码	6.3	10	16	25	35						
		0J	1A	1C	1E	1V						
0.33	R33					5X11	3.0					
0.47	R47					5X11	4.3					
0.68	R68					5X11	6.2					
1.0	010					5X11	9.1					
1.5	1R5					5X11	13.6					
2.2	2R2					5X11	19.6					
3.3	3R3					5X11	34					
4.7	4R7					5X11	38					
6.8	6R8					5X11	47					
10	100		5X11	47		5X11	60					
15	150		5X11	60	5X11	72	5X11	72	6X12	81		
22	220		5X11	72	5X11	85	6X12	94	6X12	94		
33	330		5X11	85	6X12	119	6X12	119	8X12	140		
47	470	5X11	79	6X12	119	6X12	145	8X12	162	8X12	162	
68	680	6X11	127	6X12	136	8X12	196	8X12	196	10X13	213	
100	101	6X12	153	8X12	196	8X12	238	10X13	255			
150	151	6X12	213	8X12	238	10X13	315					
220	221	8X12	264	10X13	315							
330	331	10X13	340									

SH 高精度稳定品 (CD117型)

- 低损耗角正切，高稳定的性能。
Extremely low dissipation factor, high stability.
- 适用于电视聚焦、振荡、定时回路。
Used in TV focusing locus, oscillation frequency and timer circuits.



项目	Item	特性						Characteristics						
尺寸及其误差 Size and its tolerance		ΦD	6	8	10	13	16	18	≥Φ8的漏 ≥Φ8 with safety vent PVC塑壳 PVC sleeve					
		F=0.5	2.5	3.5	5.0	7.5								
		Φd±0.1		0.5		0.6		0.8						
		α		1.0		1.5		2.0						
		β		0.5		0.8		1.0						
工作温度范围	Operating temperature range	-40 ~ +85°C												
额定电压范围	Rated voltage range	10V~50V DC												
静电容量范围	Nominal capacitance tolerance	0.47 μF ~ 470 μF												
静电容量误差	Capacitance tolerance	±10% (100Hz · 20°C)												
漏电流 (20°C)	I _L Leakage current (20°C)	I _L ≤ 0.01CV 或 0.3 μA (取其较大值) 1分钟						I _L ≤ 0.01CV 或 0.3 μA (whichever is greater) after 1 minute						
		1μF 标称静电容量	10	16	25	35	50	100Hz						
损耗角正切	tg δ (MAX)	tg δ (MAX)						0.1	0.08	0.08	0.07	0.07	20°C	
		温度						容量变化率20°C Capacitance change rate						
温度特性	Temperature characteristics (impedance ratio at 100Hz)	-40°C						+20%以内 > +20%						
		+85°C						0.21						
高温负特性	Endurance	85°C 施加额定电压1000小时，恢复16小时后电容容量应满足下表： After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:												
		静电容量变化						在初期值的 ±10% 范围内						Within ±10% of the initial measured value
		漏电流						≤ 初期规定值的150%						≤ 150% of the initial specified value
高温贮存特性	Shelf life	85°C 贮存500小时，恢复16小时后电容容量应满足下表： After storage for 500 hours at 85°C then resumed 16 hours:												
		静电容量变化						在初期值的 ±10% 范围内						Within ±10% of the initial measured value
		漏电流						≤ 初期规定值的200%						≤ 200% of the initial specified value

		DXL (mm)									
C (μF)	代码	10	16	25	35	50					
		1A	1C	1E	1V	1H					
0.47	R47										
1.0	010										
2.2	2R2										
3.3	3R3										
4.7	4R7		6X12	6X12	6X12	8X12					
10	100		6X12	8X12	10X13	10X13					
22	220		8X12	10X13	10X16	10X20					
33	330		10X13	10X16	10X20	13X20					
47	470		10X16	10X20	13X20	13X25					
100	101		10X20	13X20	13X25	16X25					
220	221		13X20	13X25	16X25	16X32					
330	331		16X25	16X25	16X32						
470	471		13X36	13X36							

TN 宽温无极性品 (CDS型)

- 105°C, 极性可反转或变换、标准尺寸。
105°C, the polarity can be reversed, standard size.
- 适用于有线电视水平偏转电流校正电路。
Used in S correction of horizontal deflection current TVs.



项目	Item	特性 Characteristics						
尺寸及其误差 Size and its tolerance		ΦD	5	6.3	8	10	≥Φ8的插孔 ≥Φ8 hole safety vent PVC塑壳 PVC case	
		F=0.5	2	2.5	2.5	5.0		
		Φd±0.1		0.5		0.6		
		α		1.0		1.5		
		β		0.5		0.8		
工作温度范围	Operating temperature range	-40 ~ +85°C						
额定电压范围	Rated voltage range	10V~3MDC						
静电容量范围	Nominal capacitance tolerance	0.33 μF ~ 330 μF						
静电容量误差	Capacitance tolerance	±20% (100Hz ~ 20°C)						
漏电流 (20°C)	I _允 漏电流 Leakage current	1分钟 I≤0.03CV 或 0.3 μA (取其较大值) 1分钟 I≤0.03CV 或 0.3 μA (whichever is greater) after 1 minute						
		C:标准静电容量	V:额定工作电压					
损耗角正切	tg δ (MAX)	额定电压 (V) Rated voltage (V)	10	16	25	35	50	100Hz
		20°C	0.15	0.12	0.10	0.08	0.08	20°C
温度特性	Z: -25°C/Z: +20°C	10	16	25	35	50	100Hz	
		2	2	1.5	1.5	1.5		
高温负特性	85°C, 施加额定电压2000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 2000 hours at 85°C then resumed 16 hours:	静电容量变化	在初期值的 ±15% 范围内 Within ±15% of the initial measured value					
		tg δ	≤初期规定值的150% ≤150% of the initial specified value					
高温贮存特性	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:	静电容量变化	在初期值的 ±15% 范围内 Within ±15% of the initial measured value					
		漏电流	≤初期规定值的200% ≤200% of the initial specified value					

		DXL (mm)					
C (μF)	代号	6.3	10	16	25	35	
		DJ	TA	TC	TE		IV
0.33	R33						5X11 3.0
0.47	R47						5X11 4.3
0.68	R68						5X11 6.2
1.0	O10						5X11 9.1
1.5	R15						5X11 13.6
2.2	2R2						5X11 19.6
3.3	3R3						5X11 34
4.7	4R7						5X11 38
6.8	6R8			5X11 38			5X11 47
10	100		5X11 47				5X11 60
15	150		5X11 60	5X11 72	5X11 72		6X12 81
22	220		5X11 72	5X11 85	6X12 94		6X12 94
33	330		5X11 85	6X12 119	6X12 119		8X12 140
47	470	5X11 79	6X12 119	6X12 145	8X12 162		8X12 162
68	680	6X11 127	6X12 136	8X12 196	8X12 196		10X13 213
100	101	6X12 153	8X12 196	8X12 238	10X13 255		
150	151	6X12 213	8X12 238	10X13 315			
220	221	8X12 264	10X13 315				
330	331	10X13 340					φDxL 瓷壳 陶瓷 (mA)

SK 高可靠标准品 (CD110型)

- 性能稳定、可靠、标准尺寸。
Reliable and stable characteristics, standard size.
- 适用于彩电、显示器、VCD机及音响等。
Used in color TV, display, VCD sets, audio sets, etc.



项目	Item	特性 Characteristics											
尺寸及其误差 Size and its tolerance		ΦD	5	6	8	10	13	16	18	20	22	25	≥Φ8的插孔 ≥Φ8 hole safety vent PVC塑壳 PVC case
		F=0.5	2	2.5	3.5	5.0	7.5	10	12.5				
		Φd±0.1		0.5		0.6		0.8					
		α		1.1		1.5		2.0					
		β		0.5		0.8		1.0					
工作温度范围	Operating temperature range	-40 ~ +85°C						-25 ~ +85°C					
额定电压范围	Rated voltage range	63V~10MDC						160V~316VDC					
静电容量范围	Nominal capacitance tolerance	0.1 μF ~ 10000 μF						0.1 μF ~ 220 μF					
静电容量误差	Capacitance tolerance	-10% ~ +30%, ±20% (100Hz ~ 20°C)											
漏电流 (20°C)	I _允 漏电流 Leakage current	I≤0.01CV 或 3 μA 1分钟 I≤0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater) (取其较大值) (whichever is greater)											
		C:标准静电容量	V:额定工作电压										
损耗角正切	tg δ	额定电压 (V) Rated voltage (V)	63	10	16	25	35	50	63-100	160	250		
		20°C	0.24	0.22	0.16	0.14	0.12	0.10	0.08	0.16	0.18		
浪涌电压 (V)	浪涌电压 (V) Surge voltage (V)	20°C	63	10	16	25	35	50	63	100	160	250	
		20°C	8	13	20	32	44	63	79	125	200	300	
温度特性	Z: -25°C/Z: +20°C	10	16	25	35	50	63	100	160	250			
		4	3	3	2	2	2	2	2	2	3		
高温负特性	85°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 85°C then resumed 16 hours:	静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value										
		tg δ	≤初期规定值的150% ≤150% of the initial specified value										
高温贮存特性	85°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 85°C then resumed 16 hours:	静电容量变化	在初期值的 ±20% 范围内 Within ±20% of the initial measured value										
		漏电流	≤初期规定值的200% ≤200% of the initial specified value										
备注	Note	如有需要, 可提供引线成型品或编带品 The products can be forming or taping if customer need											

SK 高可靠标准品 (CD110型)

- 外型尺寸 Case size
- 允许纹波电流 Permmit ripple current

		6.3		10		16		25		25		35	
		0J		1A		1C		1E		1V		1V	
C (μF)	代码	DXL (mm)											
6.8	6R8							5X11	24				
10	100					5X11	20	5X11	36	5X11			32
22	220			5X11	37	5X11	41	5X11	44	5X11			52
33	330	5X11	41	5X11	46	5X11	51	5X11	60	5X11			64
47	470	5X11	50	5X11	54	5X11	67	5X11	70	5X11			85
68	680	5X11	60	5X11	72	5X11	90	5X11	95	6X12			115
100	101	5X11	80	5X11	85	6X12	110	6X12	110	6X12			140
220	221	5X11	136	6X12	143	8X13	180	8X12	220	10X13			270
330	331	6X12	187	8X12	200	8X12	250	10X13	300	10X16			350
470	471	8X12	213	8X12	280	10X13	330	10X16	400	10X20			480
680	681	10X13	340	10X16	360	10X20	450	13X20	475	13X25			600
1000	102	10X36	400	10X16	480	10X20	550	13X20	720	13X25			750
2200	222	10X16	700	13X20	850	13X25	900	16X25	1200	16X32			1300
3300	332	13X20	950	13X25	1100	16X25	1200	16X32	1500	18X36			1572
4700	472	13X25	1100	16X25	1300	16X32	1600	18X36	1736				
6800	682	16X25	1400	16X32	1600	18X36	1954						
10000	103	16X32	1800	18X36	2119								

		6.3		100		160		200		250	
		1J		2A		2C		2D		2E	
C (μF)	代码	DXL (mm)									
0.1	0R1	5X11	3			5X11	4	6X12	3.3	6X12	3.1
0.22	R22	5X11	5			5X11	6	6X12	4.9	6X12	4.7
0.33	R33	5X11	6			5X11	7	6X12	6.0	6X12	5.7
0.47	R47	5X11	8			5X11	8	6X12	7.2	6X12	6.8
1	010	5X11	10			5X11	12	6X12	9	6X12	11
2.2	2R2	5X11	16			5X11	18	6X12	16	8X12	18
3.3	3R3	5X11	20			5X11	22	6X12	21	10X13	25
4.7	4R7	5X11	24	5X11	25	5X11	29	8X12	30	10X13	30
6.8	6R8	5X11	29	5X11	34	5X11	40	10X13	36	10X20	40
10	100	5X11	35	5X11	41	6X12	50	10X13	40	10X20	53
22	220	5X11	58	6X12	70	8X12	80	10X20	75	13X25	100
33	330	6X12	80	6X12	85	8X12	110	13X20	103	13X25	125
47	470	6X12	95	8X12	110	10X13	140	13X25	149	16X25	163
68	680	8X12	130	8X12	160	10X20	190	16X25	179	18X32	212
100	101	8X12	180	10X13	200	13X20	220	16X25	245	18X36	310
220	221	10X13	330	10X20	340	13X25	410	18X36	323		
330	331	10X20	410	13X20	450	16X25	560				
470	471	13X20	560	13X25	560	16X32	730				
680	681	16X25	680	16X25	800						
1000	102	16X25	800	16X32	950						
2200	222	18X36	935								

DXL 纹波电流 (mA)

TR 宽温度标准品 (CD210型)

- 105°C, 标准尺寸。
105°C, standard size.
- 适用于彩显、开关电源及通讯设备等。
Used in color display, switching power supply, communication sets etc.



项目 Item	特性 Characteristics																																								
尺寸及其误差 Size and its tolerance	<table border="1"> <tr> <td>ΦD</td> <td>5</td> <td>6</td> <td>8</td> <td>10</td> <td>13</td> <td>16</td> <td>18</td> </tr> <tr> <td>F±0.5</td> <td>2</td> <td>2.5</td> <td>3.5</td> <td>5.0</td> <td></td> <td>7.5</td> <td></td> </tr> <tr> <td>Φd±0.1</td> <td>0.5</td> <td>0.6</td> <td></td> <td>0.8</td> <td></td> <td></td> <td></td> </tr> <tr> <td>α</td> <td>1.1</td> <td></td> <td>1.5</td> <td></td> <td>2.0</td> <td></td> <td></td> </tr> <tr> <td>β</td> <td>0.5</td> <td></td> <td>0.8</td> <td></td> <td>1.0</td> <td></td> <td></td> </tr> </table> <p>≥Φ6壳的焊盘 ≥Φ6壳的焊盘 PVC塑封 PVC case</p>	ΦD	5	6	8	10	13	16	18	F±0.5	2	2.5	3.5	5.0		7.5		Φd±0.1	0.5	0.6		0.8				α	1.1		1.5		2.0			β	0.5		0.8		1.0		
ΦD	5	6	8	10	13	16	18																																		
F±0.5	2	2.5	3.5	5.0		7.5																																			
Φd±0.1	0.5	0.6		0.8																																					
α	1.1		1.5		2.0																																				
β	0.5		0.8		1.0																																				
工作温度范围 Operating temperature range	-40 ~ +105°C																																								
额定电压范围 Rated voltage range	6.3V~10VDC																																								
静电容量范围 Nominal capacitance tolerance	0.1 μF ~ 10000 μF																																								
静电容量误差 Capacitance tolerance	±20% (100Hz ~ 20°C)																																								
漏电流 (20°C) Leakage current (20°C)	<table border="1"> <tr> <td>I ≤ 0.10CV 或 3 μA 1分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)</td> <td>I ≤ 0.03CV 或 10 μA 3分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)</td> </tr> </table>	I ≤ 0.10CV 或 3 μA 1分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)	I ≤ 0.03CV 或 10 μA 3分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)																																						
I ≤ 0.10CV 或 3 μA 1分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)	I ≤ 0.03CV 或 10 μA 3分钟 I ≤ 0.03CV 或 10 μA 3分钟 (取其较大值) (whichever is greater)																																								
I: 允许漏电流 Leakage current	C: 标准静电容量 Nominal capacitance																																								
V: 额定工作电压 Rated voltage																																									
额定电压 (V) Rated voltage (V)	63 10 16 25 35 50 63 100 160~250																																								
tg δ	0.28 0.24 0.20 0.16 0.14 0.10 0.08 0.20																																								
静电容量大于1000 μF者, 每增加1000 μF, tg δ 增加0.02 When capacitance is more than 1000 μF, tg δ will add 0.02 per 1000 μF addition.																																									
浪涌电压 (V) Surge voltage (20°C)	<table border="1"> <tr> <td>额定电压 (V) Rated voltage (V)</td> <td>6</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> <td>160, 250</td> </tr> <tr> <td>浪涌电压 (V) Surge voltage (V)</td> <td>8</td> <td>13</td> <td>20</td> <td>32</td> <td>44</td> <td>63</td> <td>79</td> <td>125</td> <td>200, 300</td> </tr> </table>	额定电压 (V) Rated voltage (V)	6	10	16	25	35	50	63	100	160, 250	浪涌电压 (V) Surge voltage (V)	8	13	20	32	44	63	79	125	200, 300																				
额定电压 (V) Rated voltage (V)	6	10	16	25	35	50	63	100	160, 250																																
浪涌电压 (V) Surge voltage (V)	8	13	20	32	44	63	79	125	200, 300																																
温度特性 Temperature characteristics (impedance ratio at 100Hz)	<table border="1"> <tr> <td>额定电压 (V) Rated voltage (V)</td> <td>6</td> <td>4</td> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Z-25°C/Z+20°C</td> <td>5</td> <td>4</td> <td>3</td> <td></td> <td></td> <td>2</td> <td></td> <td></td> <td>3</td> </tr> <tr> <td>Z-40°C/Z+20°C</td> <td>10</td> <td>6</td> <td>6</td> <td>4</td> <td></td> <td></td> <td>3</td> <td></td> <td>4</td> </tr> </table>	额定电压 (V) Rated voltage (V)	6	4	3							Z-25°C/Z+20°C	5	4	3			2			3	Z-40°C/Z+20°C	10	6	6	4			3		4										
额定电压 (V) Rated voltage (V)	6	4	3																																						
Z-25°C/Z+20°C	5	4	3			2			3																																
Z-40°C/Z+20°C	10	6	6	4			3		4																																
高温负荷特性 Endurance	<p>105°C, 施加额定电压1000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage for 1000 hours at 105°C then resumed 16 hours:</p> <table border="1"> <tr> <td>静电容量变化 Capacitance change</td> <td>在初期值的±20%范围内</td> <td>Within ±20% of the initial measured value</td> </tr> <tr> <td>tg δ</td> <td>≤初期规定值的150%</td> <td>≤150% of the initial specified value</td> </tr> <tr> <td>漏电流 Leakage current</td> <td>≤初期规定值</td> <td>≤initial specified value</td> </tr> </table>	静电容量变化 Capacitance change	在初期值的±20%范围内	Within ±20% of the initial measured value	tg δ	≤初期规定值的150%	≤150% of the initial specified value	漏电流 Leakage current	≤初期规定值	≤initial specified value																															
静电容量变化 Capacitance change	在初期值的±20%范围内	Within ±20% of the initial measured value																																							
tg δ	≤初期规定值的150%	≤150% of the initial specified value																																							
漏电流 Leakage current	≤初期规定值	≤initial specified value																																							
高温贮存特性 Shelf life	<p>105°C, 贮存500小时, 恢复16小时后电容容量应满足下表: After storage for 500 hours at 105°C then resumed 16 hours:</p> <table border="1"> <tr> <td>静电容量变化 Capacitance change</td> <td>在初期值的±20%范围内</td> <td>Within ±20% of the initial measured value</td> </tr> <tr> <td>tg δ</td> <td>≤初期规定值的150%</td> <td>≤150% of the initial specified value</td> </tr> <tr> <td>漏电流 Leakage current</td> <td>≤初期规定值的200%</td> <td>≤200% of the initial specified value</td> </tr> </table>	静电容量变化 Capacitance change	在初期值的±20%范围内	Within ±20% of the initial measured value	tg δ	≤初期规定值的150%	≤150% of the initial specified value	漏电流 Leakage current	≤初期规定值的200%	≤200% of the initial specified value																															
静电容量变化 Capacitance change	在初期值的±20%范围内	Within ±20% of the initial measured value																																							
tg δ	≤初期规定值的150%	≤150% of the initial specified value																																							
漏电流 Leakage current	≤初期规定值的200%	≤200% of the initial specified value																																							
备注 Note	如有需要, 可提供引线成型品或编带品 The products can be forming or taping if customer need																																								

TR 宽温度标准品 (CD210型)

- 外型尺寸 Case size
- 允许纹波电流 Permmit ripple current

C(μF)	代码	6.3		10		16		25		35	
		0J	1A	1A	1C	1E	1V	1V	1V	1V	1V
6.8	6R8							5X11	24	5X11	32
10	100					5X11	20	5X11	36	5X11	52
22	220			5X11	37	5X11	41	5X11	44	5X11	64
33	330	5X11	41	5X11	46	5X11	51	5X11	60	5X11	85
47	470	5X11	50	5X11	54	5X11	67	5X11	70	6X12	115
68	680	5X11	60	5X11	72	5X11	90	5X11	95	8X12	140
100	101	5X11	80	5X11	85	6X12	110	6X12	110	10X13	270
220	221	5X11	136	6X12	143	8X13	180	8X12	220	10X16	350
330	331	6X12	167	8X12	200	8X12	250	10X13	300	10X20	480
470	471	8X12	213	8X12	280	10X13	330	10X16	400	13X25	600
680	681	10X13	340	10X16	360	10X20	450	13X20	475	13X25	750
1000	102	10X36	400	10X16	480	10X20	550	13X20	720	16X32	1300
2200	222	10X16	700	13X20	850	13X25	900	16X25	1200	18X36	1572
3300	332	13X20	950	13X25	1100	16X25	1200	16X32	1500		
4700	472	13X25	1100	16X25	1300	16X32	1600	18X36	1736		
6800	682	16X25	1400	16X32	1600	18X36	1954				
10000	103	16X32	1800	18X36	2119						

C(μF)	代码	50		63		100		160		250	
		1H	1J	2A	2C	2E	2E	2E	2E	2E	2E
0.1	0R1	5X11	3			5X11	4	6X12	3.3	6X12	3.1
0.22	R22	5X11	5			5X11	6	6X12	4.9	6X12	4.7
0.33	R33	5X11	6			5X11	7	6X12	6.0	6X12	5.7
0.47	R47	5X11	8			5X11	8	6X12	7.2	6X12	6.8
1	101	5X11	10			5X11	12	6X12	9	6X12	11
2.2	2R2	5X11	16			5X11	18	6X12	16	6X12	18
3.3	3R3	5X11	20			5X11	22	6X12	21	10X13	25
4.7	4R7	5X11	24	5X11	25	5X11	29	8X12	30	10X13	30
6.8	6R8	5X11	29	5X11	34	5X11	40	10X13	36	10X20	40
10	100	5X11	35	5X11	41	6X12	50	10X13	40	10X20	53
22	220	5X11	58	6X12	70	8X12	80	10X20	75	13X25	100
33	330	6X12	80	6X12	85	8X12	110	13X20	103	13X25	125
47	470	6X12	95	8X12	110	10X13	140	13X25	149	16X25	163
68	680	8X12	130	8X12	160	10X20	190	16X25	179	18X32	212
100	101	8X12	180	10X13	200	13X20	220	16X25	245	18X36	310
220	221	10X13	330	10X20	340	13X25	410	18X36	323		
330	331	10X20	410	13X20	450	16X25	560				
470	471	13X20	560	13X25	560	16X32	730				
680	681	16X25	680	16X25	800						
1000	102	16X25	800	16X32	950						
2200	222	18X36	935							纹波电流 (mA)	

TK 宽温长寿命 (CD260型)

- 105°C, 5000小时, 低阻抗。
105°C, 5000hours, low impedance.
- 适用于有长寿命要求的电子设备。
Used in electronic equipments whose long life would be required.



项目 Item	特性 Characteristics	
尺寸及其误差 Size and its tolerance	ΦD	6 10 13 16 18
	F±0.05	3.5 5.0 7.5
	Φd±0.1	0.5 0.6 0.8
	α	1.0 1.5 2.0
	β	0.5 0.8 1.0
工作温度范围 Operating temperature range	-40 ~ +105°C	
额定电压范围 Rated voltage range	10V~63VDC	
静电容量范围 Nominal capacitance tolerance	4.7 μF ~ 4700 μF	
静电容量误差 Capacitance tolerance	±20% (100Hz · 20°C)	
漏电流 (20°C) Leakage current (20°C)	≤0.01CV或3μA (取较大值) 1分钟 ≤0.01CV或3μA (whichever is greater) after 1 minute	
损耗角正切 Dissipation factor	额定电压 (V) Rated voltage (V)	10 16 25 35 50 63 100Hz
	tg δ (MAX)	0.30 0.25 0.22 0.18 0.15 0.12 20°C
温度特性 Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V) Rated voltage (V)	10 16 25 35 50 63 100Hz
	Z-25°C/Z+20°C	3 2 2 2 2 2 2
	Z-40°C/Z+20°C	5 4 4 3 3 3 3
高温负荷特性 Endurance	105°C, 施加额定电压5000小时, 恢复16小时后电容容量应满足下表: After applying rated voltage by 5000 hours at 105°C, then measured 16 hours.	
	静电容量变化 Capacitance change	在初期值的±30%范围内 Within ±30% of the initial measured value
	tg δ	≤初期规定值的300% ≤300% of the initial specified value
	漏电流 Leakage current	≤初期规定值 ≤initial specified value
高温贮存特性 Shelf life	105°C, 贮存5000小时, 恢复16小时后电容容量应满足下表: After storage for 5000 hours at 105°C, then measured 16 hours.	
	静电容量变化 Capacitance change	在初期值的±20%范围内 Within ±20% of the initial measured value
	tg δ	≤初期规定值的150% ≤150% of the initial specified value
	漏电流 Leakage current	≤初期规定值的200% ≤200% of the initial specified value

C(μF)	代码	10 (1A)		16 (1C)		25 (1E)	
		纹波电流 Ripple current	纹波电压 Ripple voltage	纹波电流 Ripple current	纹波电压 Ripple voltage	纹波电流 Ripple current	纹波电压 Ripple voltage
47	470						
100	101	8X12	1.00	170	8X12	1.00	170
220	221	10X13	0.60	250	10X13	0.60	250
330	331	10X16	0.40	370	10X16	0.40	370
470	471	10X16	0.40	370	10X20	0.28	500
1000	102	13X20	0.16	750	13X25	0.14	800
2200	222	16X25	0.08	1250	16X25	0.08	1250
3300	332	16X32	0.07	1400	16X36	0.06	1550

C(μF)	代码	35 (1V)		50 (1H)		63 (1J)	
		纹波电流 Ripple current	纹波电压 Ripple voltage	纹波电流 Ripple current	纹波电压 Ripple voltage	纹波电流 Ripple current	纹波电压 Ripple voltage
10	100						
22	220			8X12	1.00	170	8X12
33	330	8X12	1.00	170	10X13	0.60	250
47	470	8X12	1.00	170	10X13	0.60	250
100	101	10X13	0.60	250	10X16	0.40	370
220	221	10X20	0.28	500	13X20	0.16	750
330	331	13X20	0.16	750	13X20	0.16	750
470	471	13X20	0.16	750	16X25	0.08	1250

PD 宽低温用品 (CD261型)

- 55°C ~ +105°C, 低温阻抗小。
-55°C ~ +105°C, low impedance at -55°C.
- 适用于有低温要求的电子设备。
Used in electronic equipments, its low environmental temperature is required.



项目	Item	特性 Characteristics									
尺寸及其误差 Size and its tolerance		ΦD	6	8	10	13	16	18			
		F=0.5	2.5	3.5	5.0	7.5			≥ Φ8壳的爆 ≥ Φ8 shell safety vent		
		Φd±0.1	0.5	0.6	0.8				PVC塑壳 PVC sheath		
		α	1.0	1.5	2.0						
		β	0.5	0.8	1.0						
工作温度范围	Operating temperature range	-55 ~ +105°C									
额定电压范围	Rated voltage range	6.3V ~ 10VDC									
静电容量范围	Nominal capacitance tolerance	1 μF ~ 10000 μF									
静电容量误差	Capacitance tolerance	±20% (100Hz · 20°C)									
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.01CV 或 3 μA (取较大值) 1分钟 I ≤ 0.01CV or 3 μA (whichever is greater) after 1 minute									
		I允许漏电流	Leakage current	C标准静电容量	Nominal capacitance	V额定工作电压	Rated voltage				
损耗角正切	Dissipation factor	额定电压 (V)	6.3	10	16	25	35	50	63	100	100Hz
		tg δ (MAX)	0.24	0.20	0.16	0.14	0.12	0.10	0.08	0.08	20°C
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	6.3	10	16	25	35	50	63	100	100Hz
		Z-25°C/Z+20°C	4	3	2	2	2	2	2	2	2
高温负荷特性	Endurance	105°C, 施加额定电压1000小时, 恢复16小时后静电容量应满足下表: After applying rated voltage for 1000 hours at 105°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							
高温贮存特性	Shelf life	105°C, 贮存500小时, 恢复16小时后静电容量应满足下表: After storage for 500 hours at 105°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							

DXL (mm)

C (μF)	代码	6.3	10	16	25	35	50	63	100
		0J	1A	1C	1E	1V	4H	4J	2A
1	010						6X15		
2.2	2R2						6X15		
3.3	3R3						6X15		
4.7	4R7						6X15		6X15
10	100						6X15		6X15
22	220						6X15		6X15
33	330						6X15		6X15
47	470				6X15	6X15	6X15	8X15	8X20
100	101			6X15	6X15	8X15	8X20	10X20	10X32
220	221		6X15	8X12	8X15	8X20	10X25	13X20	12X36
330	331	6X15	8X12	8X15	8X15	10X20	10X32	13X25	16X32
470	471	8X15	8X15	8X20	10X20	10X32	13X25	13X36	16X40
1000	101	10X20	10X20	10X32	13X25	13X32	16X32	16X40	
2200	221	10X32	13X25	13X32	13X40	16X36	18X40		
3300	331	13X25	13X26	13X40	16X36	18X40			
4700	472	13X36	16X32	16X36					
6800	682	16X32	16X36	18X36					
10000	103	16X40	18X40						

PH 宽高温用品 (CD262型)

- 40°C ~ +125°C, 2000小时。
-40°C ~ +125°C, 2000 hours.
- 适用于有长寿命和可靠性要求的电子设备。
Used in electronic equipments whose long life and reliability are required.



项目	Item	特性 Characteristics									
尺寸及其误差 Size and its tolerance		ΦD	8	10	13	16					
		F=0.5	3.5	5.0	7.5				≥ Φ8壳的爆 ≥ Φ8 shell safety vent		
		Φd±0.1	0.5	0.6	0.8				PVC塑壳 PVC sheath		
		α	1.0	1.5	2.0						
		β	0.5	0.8	1.0						
工作温度范围	Operating temperature range	-40 ~ +125°C									
额定电压范围	Rated voltage range	10V ~ 63VDC									
静电容量范围	Nominal capacitance tolerance	0.47 μF ~ 10000 μF									
静电容量误差	Capacitance tolerance	±20% (100Hz · 20°C)									
漏电流 (20°C)	Leakage current (20°C)	I ≤ 0.04CV 或 2 μA (取较大值) 1分钟 I ≤ 0.04CV or 2 μA (whichever is greater) after 1 minute									
		I允许漏电流	Leakage current	C标准静电容量	Nominal capacitance	V额定工作电压	Rated voltage				
损耗角正切	Dissipation factor	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		tg δ (MAX)	0.20	0.16	0.14	0.12	0.10	0.08	0.08	20°C	
温度特性	Temperature characteristics (Impedance ratio at 100Hz)	额定电压 (V)	10	16	25	35	50	63	100	100Hz	
		Z-25°C/Z+20°C	3	2	2	2	2	2	2	2	
高温负荷特性	Endurance	125°C, 施加额定电压2000小时, 恢复16小时后静电容量应满足下表: After applying rated voltage for 2000 hours at 125°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							
高温贮存特性	Shelf life	125°C, 贮存500小时, 恢复16小时后静电容量应满足下表: After storage for 500 hours at 125°C then resumed 16 hours:									
		静电容量变化	Capacitance change	在初期值的 ±20% 范围内							

DXL (mm)

C (μF)	代码	10	16	25	35	50	63
		1A	1C	1E	1V	4H	4J
0.47	R47						
1	010					8X12	8X12
2.2	2R2					8X12	8X12
3.3	3R3					8X12	8X12
4.7	4R7					8X12	8X12
10	100					8X12	10X13
22	220					8X12	10X13
33	330					8X12	10X13
47	470			8X12	10X13	10X20	10X20
100	101			10X13	8X12	10X20	13X25
220	221			10X20	10X16	13X25	16X25
330	331			13X25	13X20	16X25	
470	471			13X25	13X25		
1000	102			16X25	16X25		

PF 开关电源 (CD21T型)

- 105°C, 高频率阻抗。
105°C, low impedance for high frequency.
- 适用于开关电源、彩显等电路。
Used in switching power supply and color display circuits.



项目 Item	特性 Characteristics										
尺寸及其误差 Size and its tolerance 	ϕD	5	6	8	10	13	16	18			
	F=0.5	2	2.5	3.5	5	7.5					
	$\phi d \pm 0.1$	0.5	0.6	0.8							
	α	1.0	1.5	2.0							
	β	0.5	0.8	1.0							
工作温度范围 Operating temperature range	-40 ~ +105°C										
额定电压范围 Rated voltage range	6.3V ~ 10MDC										
静电容量范围 Nominal capacitance tolerance	0.47 μ F ~ 1000 μ F										
静电容量误差 Capacitance tolerance	$\pm 20\%$ (100Hz · 20°C)										
漏电流 (20°C) Leakage current (20°C)	I: ≤ 0.02 CV 或 5 μ A (取较大值) 1分钟 I: ≤ 0.02 CV or 5 μ A (whichever is greater) after 1 minute										
允许漏电流 I: Leakage current	C: 标称静电容量 Nominal capacitance										
损耗角正切 Dissipation factor	tg δ (MAX)										
温度特性 Temperature characteristics (Impedance ratio at 100Hz)	Z-25°C/Z+20°C	4	3	2	2	2	2	2	2	2	
	Z-40°C/Z+20°C	8	6	4	4	4	3	3	3	3	
高温负荷特性 Endurance	105°C, 施加额定电压1000小时, 恢复16小时后电容容值应满足下表: After applying rated voltage for 1000 hours at 105°C, then resumed 16 hours: 静电容量变化 Capacitance change: 在初期值的 $\pm 20\%$ 范围内 Within $\pm 20\%$ of the initial measured value 漏电流 Leakage current: \leq 初期规定值的150% $\leq 150\%$ of the initial specified value 漏电流 Leakage current: \leq 初期规定值 \leq initial specified value										
高温贮存特性 Shelf life	105°C, 贮存5000小时, 恢复16小时后电容容值应满足下表: After storage for 5000 hours at 105°C, then resumed 16 hours: 静电容量变化 Capacitance change: 在初期值的 $\pm 20\%$ 范围内 Within $\pm 20\%$ of the initial measured value 漏电流 Leakage current: \leq 初期规定值的150% $\leq 150\%$ of the initial specified value 漏电流 Leakage current: \leq 初期规定值的200% $\leq 200\%$ of the initial specified value										

C (μ F)	代码 Code	DXL (mm)									
		6.3 DC	10 DC	16 DC	25 DC	35 DC	50 DC	63 DC	100 DC		
0.47	R47							5X11		5X11	
1	010							5X11		5X11	
2.2	2R2							5X11		5X11	
3.3	3R3							5X11		5X11	
4.7	4R7							5X11		6X12	
10	100							5X11	5X11	6X12	
22	220							5X11	6X12	6X12	
33	330							5X11	6X12	6X12	
47	470		5X11		5X11	6X12	6X12	6X12	6X15	8X15	
100	101	5X11	6X12	6X12	6X15	8X12	8X20	10X20	10X32		
220	221	6X12	6X15	6X12	8X15	8X20	10X25	13X20	12X36		
330	331	6X15	8X12	8X15	8X20	10X20	10X32	13X25	16X32		
470	471	8X15	8X15	8X20	10X20	10X32	13X25	13X36	16X40		
1000	102	10X20	10X20	10X32	13X25	13X32	16X32	16X40			
2200	222	10X32	13X25	13X32	13X40	16X36	18X40				
3300	332	13X25	13X36	13X40	16X36	18X40					
4700	472	13X36	13X32	16X36	18X40						
6800	682	16X32	16X36								
10000	103	16X40	18X40								

PS 闪光灯耗材 (CD21S型)

- 低漏电、低损耗、小体积。
Low leakage current/low dissipation factor and small body.
- 适用于照相机闪光灯充电电路。
Used in flash lamp circuits in camera.



项目 Item	特性 Characteristics											
尺寸及其误差 Size and its tolerance 	ϕD	10	13	14.5	16	17	18	20	22			
	F=0.5	5.0	7.5									
	$\phi d \pm 0.1$	0.6	0.8									
	α	1.5	2.0									
	β	0.8	1.0									
工作温度范围 Operating temperature range	-20 ~ +55°C											
额定电压范围 Rated voltage range	300VDC											
静电容量范围 Nominal capacitance tolerance	20 μ F ~ 370 μ F											
静电容量误差 Capacitance tolerance	$-10\% \sim +20\%$ (100Hz/20°C)											
漏电流 (20°C) Leakage current (20°C)	I: ≤ 0.03 CV 或 10 μ A (取较大值) 1分钟 I: ≤ 0.03 CV or 10 μ A (whichever is greater) after 1 minute											
允许漏电流 I: Leakage current	C: 标称静电容量 Nominal capacitance											
损耗角正切 Dissipation factor	tg δ (MAX)											
温度特性 Temperature characteristics (Impedance ratio at 100Hz)	Z-25°C/Z+20°C											
	Z-25°C/Z+20°C	2										
高温负荷特性 Endurance	5 ~ 35°C, 以额定电压每30秒充放电一次, 5000次后电容应符合下表: After applying rated voltage 30s for charge-discharge at 5~35°C, 5000 cycles: 静电容量变化 Capacitance change: 在初期值的 $\pm 10\%$ 范围内 Within $\pm 10\%$ of the initial measured value 漏电流 Leakage current: \leq 初期规定值的150% $\leq 150\%$ of the initial specified value 漏电流 Leakage current: \leq 初期规定值 \leq initial specified value											
高温贮存特性 Shelf life	75°C, 贮存500小时, 恢复16小时后电容容值应满足下表: After storage for 500 hours at 75°C, then resumed 16 hours: 静电容量变化 Capacitance change: 在初期值的 $\pm 10\%$ 范围内 Within $\pm 10\%$ of the initial measured value 漏电流 Leakage current: \leq 初期规定值的150% $\leq 150\%$ of the initial specified value 漏电流 Leakage current: \leq 初期规定值的200% $\leq 200\%$ of the initial specified value											

C (μ F)	代码 Code	330V DC											
		$\phi 10$	$\phi 13$	$\phi 14.5$	$\phi 16$	$\phi 17$	$\phi 18$	$\phi 20$	$\phi 22$				
20	200	10x25	13x20										
40	400	10x30	13x25										
60	600		13x30	14.5x25									
80	800		13x35	14.5x30	16x25								
100	101			14.5x36	16x30	17x28							
120	121				16x36	17x33	18x30						
140	141				16x40	17x37	18x34	20x30					
160	161					17x39	18x36	20x32	22x28				
180	181					17x39	18x36	20x32	22x28				
200	201					17x48	18x40	20x34	22x32				
240	241						18x40	20x40	22x36				
370	371								22x45				


测试方法 (A) Test method

Capacitance test method
容量测试方法

A1、测试装置 Test Device:

电容测试仪: 测量频率100±5HZ、(测量精度±2%)
专用测试夹具: 测试液容量~500ml、(测试液深度~80mm)
Capacitance tester: measuring frequency (100±5HZ, the measurement accuracy of +/ - 2%)
Special test fixture: test liquid capacity to 500ml (test, liquid depth ~ 80mm)

A2、测试电路 Test Circuit: (见图A1)



A3、测试液 Test fluid:

纯水 Pure water: 1000ml
己二酸铵 Adipic acid ammonium: 150g (电极级)
电阻率 Resistivity: 6.5 ± 0.5 $\Omega \cdot \text{cm}$ (70±2℃)
PH值 Value of Ph: 6.7 ± 0.5 (50±2℃)

A4、试样 Sample:

将经过氧化膜耐压及升压时间测试的试样作为本测试用的试样。
The oxide film through sample testing pressure and boost time as the test sample for.

A5、测定程序 Measuring program:

- 将试样夹在专用夹具上, 测试部分放入测试液面以下, 试样以边缘与液面相平或浸入液面不超过1mm。
 - 测试温度30±2℃。
 - 从电容测试仪上读出的电容量数值除以5为该箔的比电容 ($\mu\text{f}/\text{cm}^2$)。
- The sample holder in special jig, the testing part into the test specimen with edge below the surface of the liquid, and liquid surface is flat or immersed in liquid level does not exceed 1mm.
 - The test temperature of 30 plus or minus 2 deg.
 - The capacitance value divided by the readout from the capacitance tester on the 5 as the foil specific capacitance ($\mu\text{f}/\text{cm}^2$).

A6、说明 Explain:

- 测试液每周更换一次, 如发生异常立即更换。
 - 一般性检测, 测试温度范围可放宽到15~32℃。
- The test solution was changed weekly, such as abnormal replaced immediately.
 - general test, test temperature range can be widened to 15~32 DEG.C.

Aluminium Foils for
Aluminium Capacitor
低压化成铝箔

低压化成箔规格表

Low pressure formed foil specification table

型号 Model	厚度 (μm)	7	8	9	10	11	13	14	16	17	18	19	21	23	28	29	31	33	36	41	43	46	51	61	62	66	72	85	
J00L/A40	90	—	—	—	—	—	—	—	91	83	81	77	67	62	48	45	42	38	34	—	—	—	—	—	—	—	—	—	—
J00L/A41	90	—	—	—	—	—	—	—	94	96	84	80	70	64	50	47	44	40	36	—	—	—	—	—	—	—	—	—	—
J05L/A40	95	206	195	165	145	135	110	100	94	96	84	80	68	64	50	47	44	40	36	—	—	—	—	—	—	—	—	—	—
J05L/A41	95	210	200	170	150	140	115	103	96	88	86	83	71	66	55	49	46	42	38	—	—	—	—	—	—	—	—	—	—
J05L/A42	95	215	205	175	155	145	120	107	98	90	88	85	75	68	54	51	48	44	40	—	—	—	—	—	—	—	—	—	—
J05L/A43	95	220	210	180	160	150	125	110	100	92	90	87	78	70	56	53	50	46	42	—	—	—	—	—	—	—	—	—	—
J100L/A43	100	—	—	—	—	—	—	—	100	92	90	87	78	70	56	53	50	46	42	34	31	28	27	18	17.5	15	12.5	10.5	
J100L/A44	100	—	—	—	—	—	—	—	105	96	93	90	81	72	58	56	52	48	44	36	34	31	28	19	18.5	16	13.5	11.5	
J100L/A45	100	—	—	—	—	—	—	—	110	100	96	92	84	75	60	58	54	50	46	38	36	33	29	20	19.5	17	14.5	12.5	

注: 客户需列表以外特别注明规格方为有效生产。
Note: customer's need to list outside this specification can be produced by both parties agreed upon.

测试方法 (B) Test method

Film pressure and boost time testing method 氧化膜耐压及升压时间测试方法

B1、测试装置 Test Device:

直流恒流电源: 恒流精度 $\leq \pm 3\%$ 纹波电流 $\leq 2\%$

直流电压表: 内阻 $\geq 1M$ 值准确度 $\pm 0.5\%$

直流电流表: 内阻远小于负载阻值, 准确度 $\pm 1\%$

电压记录仪: 内阻 $\geq 1M$ 值准确度 $\pm 0.5\%$

预定槽: 容积 $\sim 500ml$, 深度 $\sim 100mm$, 材料为不锈钢 (1Cr18Ni9Ti)

温度计: 量程 $100^{\circ}C$ 、精度 $\pm 1^{\circ}C$

秒表: 精度 ± 1 秒

DC constant current power supply, the precision of constant current ripple accuracy is less than or equal to 2% and less than 3%

DC voltmeter: resistance is greater than or equal to 1M accuracy = 0.5%

The DC ammeter: resistance is far less than the load resistance, the accuracy of plus or minus 1%


Voltage recorder: resistance is greater than or equal to 1M accuracy = 0.5%

Determination of trough: volume of $\sim 500ml$, $\sim 100mm$ depth, materials for stainless steel (1Cr18Ni9Ti)

Thermometer: ranging of $100^{\circ}C$, the accuracy of plus or minus 1 deg.

Stopwatch: accuracy of ± 1 second

B2、测试电路 Test Circuit: (见图B1)



图B1. 氧化膜耐压测试电路图

B3、测试液 Test fluid:

纯水 Pure water: 1000ml


己二酸铵 Adipic acid ammonium: 150g (电容倍)

电阻率 Resistivity: $6.5 \begin{matrix} +2.0 \\ -1.5 \end{matrix} \Omega \cdot cm (70 \pm 2^{\circ}C)$

Ph值 Value of Ph: $6.7 \begin{matrix} +0.5 \\ -1.5 \end{matrix} (60 \pm 2^{\circ}C)$

B4、试样尺寸及取样位置 Sample size and sampling locations:

a. 试样尺寸 Sample size (见图B2)



图B2. 试样尺寸示意图
Fig. B2. sample size

b. 取样位置 Sampling location (见图B3)



图B3. 取样位置示意图
Fig. B3. Sketch map of sampling locations

左、右、中三个部位, 各取1张试样测试。
The three part, left, right, each take 1 sample test.

B5、测定程序 Measuring program:

- 将各部位的试样浸入试液内, 被测部分 ($10 \times 50mm$) 低于液面 $6 \sim 8mm$, 液温 $85 \pm 2^{\circ}C$ 。
- 通过电流 $1 \pm 0.1mA$, 从通过开始升至规定电压 (V_r), 所用时间记录为升压时间 (T_r)。
- 到达规定电压后 180 ± 5 秒时达到电压值记录为氧化膜耐压值 (V_t) (见图B4)。
- 加负电压氧化膜耐压值 (V_t) 为升压 120 时读取的电压值。



图B4. 升压时间和氧化膜耐压测试示意图

A. Each part of the sample was immersed in the test solution, the measured part ($10 \times 50mm$) below the level of $6 \sim 8mm$, liquid temperature of 85 plus or minus 2 deg.

B. The current $1 \pm 0.1mA$, from a specified voltage to start (V_r), the time used by the record for the rise time (T_r).

C. To achieve the voltage value recorded for the film pressure value reached the predetermined voltage after 180 ± 5 seconds (± 0.1 level (5s)).

D. Pressure anode foil film pressure value (V_t) voltage record as a boost of 120 when the value of.

B6、说明 Explain:

- 试样表面不得污染, 试样边缘光滑无毛刺。 The surface of the specimen shall not be polluted, the edge of the sample is smooth without burr.
- 测试液应每5天更换一次, 如遇异常立即更换。 The test liquid should be replaced once every 5 days, in case of abnormal replaced immediately.

测试方法 (C) Test method

Film pressure and boost time testing method 氧化膜耐压及升压时间测试方法

C1、测试装置 Test Device: 拉力试验机: 精度 $\pm 0.2N$ Tensile testing machine: accuracy $\pm 0.2N$


C2、试样尺寸及取样位置 Sample size and sampling locations:

a. 试样尺寸 Sample size: (见图C1)



图C1. 试样尺寸示意图
Fig. C1. sample size

b. 取样位置 Sampling location: (见图C2)




图C2. 取样位置示意图 Fig. C2. Sketch map of sampling locations

在箔宽中心部位取5个试样。 Take 5 samples in a site wide foil center.

C3、测定程序 Measuring program:

- 将试样按（图C3）装在拉力试验机夹具上。 According to a, the sample (Figure C3) installed in the fixture for tensile testing machine.
 - 以 (10 ± 1) mm/min或 (200 ± 20) mm/min的速度拉伸试样。
 - 记下试样断裂时的拉力即为该试样的抗拉强度，如断裂在夹持处需重新试验。
 - 取5个试样的抗拉强度平均值作为该样品的抗拉强度。
- B, in (10 ± 1) mm/min and (200 ± 20) velocity tensile specimen mm/min.
 C, Write down the test specimens for tensile strength tension is the sample, such as fracture in the clamping department need to re test.
 D, Tensile strength and take the average of 5 specimen as the tensile strength of the sample.



图C3、试样在拉力试验机上的位置图
 Location map of the specimen in the tensile testing machine.

C4、说明 Explain:

- 试样应平整，不得扭曲或有裂口。
 - 一般性测试可在5张试样中随机抽取一张测定其抗拉强度如合格即作为该样品的抗拉强度合格，如不合格则按原程序测定。
- A, The specimens should be smooth, no distortion or cracks.
 B, General test in 5 samples randomly selected from a determination of the tensile strength such as qualified as the tensile strength of the sample such as qualified, unqualified according to the original procedure determination.

测试方法 (D) Test method

Testing method for bending strength 折弯强度测试方法

D1、测试装置 Test Device: 自动折弯试验机 Automatic bending testing machine


D2、试样尺寸及取样位置 Sample size and sampling locations:

- 试样尺寸 Sample size: (见图D1)



图D1. 试样尺寸示意图
 Fig. D1. sample size

- 取样位置 Sampling location: (见图D2)



图D2、取样位置示意图 Fig. D2. Sketch map of sampling locations

在箔宽中心部位取5个试样。 Take 5 samples in a side wide foil center.

D3、测定程序 Measuring program:

- 将试样二端如（图D3）夹持在自动折弯试验机上，负载力为 $2.5N \pm 0.05N$ ，曲率半径为 $R0.5mm \pm 0.05mm$ ，弯曲角度 $90^\circ \pm 2^\circ$ ，弯曲速度6次/秒。
 The two end as the specimen (Fig. D3) is clamped on the automatic bending testing machine, the load force is $2.5N \pm 0.05N$. Curvature radius of $R0.5mm \pm 0.05mm$, the bending angle of 90 degrees plus or minus 2 degrees, the bending speed is 6 times / sec.

- 启动自动折弯试验机，直至试样片折断为止，记录下显示器显示的数字，即为该试样的折弯强度。（不在规定的夹持处断裂应重新测试）
 To start the automatic bending test machine, until the test piece break, record the display numbers, is the bending strength of the specimen. (not in the specified clamping rupture should be re tested)

Bending number five Zhang sample average value of bending strength of the samples (times).


- 五张试样的折弯次数平均值为该样品的折弯强度（次数）。

D4、说明 Explain:

- 试样应平整，不得扭曲或有裂口。
- 一般性测试可在5张试样中随机抽取一张测定其折弯强度如合格即作为该样品的折弯强度合格，如不合格则按原程序测定。

A, The specimens should be smooth, no distortion or cracks.

B, General test in 5 samples randomly selected from a determination of the bending strength such as qualified as bending strength of the samples such as qualified, unqualified according to the original procedure determination.



图D3、试样在试验装置中的位置图
 Location map of the test piece in the test device

测试方法 (E) Test method

Methods the concentration of chlorine ion test the residual surface 表面残留氯离子浓度测试方法

E1、试验装置 Test device:

离心机: 转速 ≥ 3000 转/分	Centrifuge: Speed ≥ 3000 rev / min
离心管: 50ml	Tube: 50ml
三角烧瓶: 100ml	Erlenmeyer flask: 100ml
吸管: 5ml	Straw: 5ml
量杯: 100ml	Cup: 100ml
比浊度: 有20ml刻度线	Turbidity ratio: There 20ml tick
恒温水浴槽: 容积2L以上、 $80^\circ C \pm 5^\circ C$ 、 $30^\circ C \pm 2^\circ C$ 。	Constant temperature water bath: 2L above volume, $80^\circ C \pm 5^\circ C$, $30^\circ C \pm 2^\circ C$.
冷却槽: 容积3L以上	Cooling tank: 3L volume above
比浊装置: 附有荧光灯的暗箱	Turbidity unit: black box with fluorescent
温度计: 量程 $100^\circ C$ 精度 $\pm 1^\circ C$	Thermometer: Range $100^\circ C$ Accuracy $\pm 1^\circ C$

E2、测定试剂 Assay reagent:

氢氧化钠水溶液: 氢氧化钠 (特级试剂) 2g 溶于 1L 纯水中。
硝酸银水溶液: 硝酸银 (特级试剂) 2.5g 溶于 500ml 纯水中。
60% 硝酸: 特级试剂 ($\rho < 0.5 \text{ mg/L}$)

1mg/L 氯离子基准液: 氯化钠 (特级试剂) 经 1.20°C 2 小时干燥后称取 1.65g 溶于 1L 纯水中, 再取 1ml 稀释为 1L。

Aqueous sodium hydroxide solution: sodium hydroxide (special grade reagent) 2g dissolved in 1L of pure water.

Aqueous silver nitrate solution: Silver nitrate (special reagent grade) 2.5g dissolved in 500ml of pure water.

60% nitric acid: special grade reagent ($\rho < 0.5 \text{ mg/L}$)

1mg/L chloride reference solution: sodium chloride (special grade reagent) through 1.20°C 2 hours after drying weighed 1.65g dissolved in 1L of pure water, and then take 1ml diluted to 1L.


E3、试样尺寸及取样位置 Sample size and sampling locations:

a. 试样尺寸 Sample size:



截取面积为 125cm² 左右 (~100 × 125mm) 的长方形试样, 再剪成 1cm² 左右的小片, 全部作试验用。
Interception area is about 125cm² (~100 × 125mm) rectangular test piece, and then torn into small pieces of about 1cm², all for test.

b. 取样位置 Sampling location:



试样在箔中央部位截取。
In the central portion of the foil test piece interception.

E4、测定程序 Measuring program:

- 将 125cm² 试样, 剪成 1cm² 左右的小片放入 100ml 三角瓶中, 加入 60ml 氢氧化钠水溶液, 搅拌后在室温下放置约 7 分钟。
- 将上述液体倒入 100ml 量杯, 并用 10ml 纯水清洗三角瓶 2 次一起倒入量杯, 加入 6.0% 硝酸 3ml, 放入 80°C ± 1.0°C 恒温水浴槽内 20 分钟取出冷却至室温后加入纯水至 100ml 刻度线, 摇晃均匀。
- 将量杯内的液体倒出 30~40ml 放在离心机上分离 15 分钟后, 取上面清液 20ml 倒入比浊管内待用。
- 取 1mg/L 氯离子基准液 2ml 稀释至 20ml 作为比浊标准 (相当于残留氯离子浓度 0.8mg/M)。
- 将装有比浊标准液和试样液在比浊管内每管加入 60% 硝酸约 1ml, 摇晃均匀后再加入 2ml 硝酸银水溶液摇晃均匀后移入比浊装置内比较浊度。

f. 试样液浊度低于比浊标准液判为合格, 反之不合格。

- The 125cm² test piece, torn into small pieces of about 1cm² 100ml flask, 60ml of aqueous sodium hydroxide solution, allowed to stand at room temperature after stirring for about 7 minutes.
- After adding the liquid is poured into pure 100ml beaker, flask and wash twice with 10ml water together into the measuring cup, add 6.0% 3ml nitric acid, into the 80°C ± 1.0°C constant temperature aqueous bath 20 minutes then cool to room temperature. 100ml water to the mark, shake well.
- The amount of liquid poured inside 30~40ml mark on the centrifuge for 15 minutes, take 20ml pour the clear liquid above the cloud than the inner tube stand.
- Take 1mg/L chloride reference solution 2ml diluted to 20ml as turbidity standard (equivalent to the residual chlorine ion concentration 0.8mg/M).
- Will be equipped with turbidity standard solution and sample solution turbidity tube with 60% nitric acid was added to each tube about 1ml, 2ml shake well before adding silver nitrate solution into relatively Shake turbidity than the inner cloud devices.
- Sample turbidity is less than turbidity standard solution for qualified, unqualified and vice versa.

E5、说明 Explain:

- 试验所用滤液器具皆应用纯水仔细清洗干净。
- 所用试剂、纯水都要确认所含氯离子达到要求方可使用。
- 对比过程应在加入硝酸银试剂后 1~3 分钟内完成。

A. Instruments used in the test solution containing water are applied carefully cleaned.
B. The reagents, water must meet the requirements to confirm the chlorine ions can be used.
C. Turbidimetric procedure should be completed after addition of the silver nitrate reagent within 1 to 3 minutes.

测试方法 (F) Test method

Water resistance test methods 耐水性试验方法

F1、测试装置 Test Device:

烧杯: 500ml Beaker: 500ml
恒温水浴槽: 容积 2 升以上, 恒温 95~98°C Constant temperature water bath: Volume 2 liters or more, thermostat 95~98°C

F2、试样尺寸及取样位置 Sample size and sampling locations:



b. 试样位置 Sampling location



A. The sample Vt measured by test method B. Tr.
B. Was added 500ml of pure water in a beaker, and heated in a constant temperature water bath to 95~98°C.

F3、测定程序 Measuring program:

- 将试样按测试方法 B 测定 Vt. Tr。
- 在烧杯中加入纯水 500ml, 并在恒温水浴槽中加热到 95~98°C。
- 将测量过 Vt 的试样用纯水洗净放入已达到规定温度的纯水中并保持 60 ± 1min。
- 将经过处理的试样再按测试方法 B 测定到达 0.5Vt 的升温时间 Tr60。

C. The sample was washed with pure water and measured the Vt placed in pure water has reached a predetermined temperature and held 60 ± 1min.
D. After processing the samples then determined to reach 0.9Vt Test Method B Boost time Tr60.

F4、说明 Explain:

- 纯水电阻率 ≥ (MQ cm)。
- 每次 500ml 纯水中最多处理 6 张试样。
- 处理水温要严格控制, 防止沸水气泡损坏试样箔。

A. Water resistivity ≥ (MQ cm).
B. 500ml water in each process: up to 6 samples.
C. Processing temperature must be strictly controlled to prevent damage to the specimen boiling bubble fol.